

# DECK CONVERSION

Date: \_\_\_\_\_ Salesperson: \_\_\_\_\_

Customer Name: \_\_\_\_\_ Customer Site: \_\_\_\_\_

## NEW PRODUCT SPECIFICATIONS

Attachment Style:  Polydeck® Pin & Leg    Open Area:  Maximum (MOA)  Standard (SOA)

Tema     Linatex® Snapdeck® Classic    Other \_\_\_\_\_

Panel Size (X,Y):  1' x 1'     1' x 2'     1' x 4'    Other \_\_\_\_\_

Opening: \_\_\_\_\_ Material:  Urethane     Rubber

Opening Shape Type:  Square     Slotted     Zig-Zag     Brick     Round

Web Type:  Standard     Flex     Heavy     Light    Other \_\_\_\_\_

Slot Direction:  With Flow     Against Flow

## EXISTING SPECIFICATIONS

Current Annual Usage: \_\_\_\_\_ Current Panel Life: \_\_\_\_\_

Current Issues: \_\_\_\_\_ Current Manufacturer: \_\_\_\_\_

## APPLICATION INFORMATION

Factory or In-Field Installation:  Yes     No

Machine Mfg No: \_\_\_\_\_ Screening Material: \_\_\_\_\_

Application:  Dry     Wet    Spray Bars:  Yes     No

Feed Rate: \_\_\_\_\_ TPH    Avg Running per Week: \_\_\_\_\_ hrs

Material Feed Size: \_\_\_\_\_ Drop Height: \_\_\_\_\_

Working Temperature:  Ambient     >170°F     < 40°F    Humidity: \_\_\_\_\_

Deck Size: Width = \_\_\_\_\_ Length = \_\_\_\_\_ Wall to Wall Dimension: \_\_\_\_\_